

屋内照明器具特性	
品番 (品名)	X F L 3 2 3 S C
光源	LDL40S. N / 14 / 26 (2 6 0 0 A) × 2 2 6 0 0 . 0 l m
管理番号	K 0 1 2 6 1 4 3 (1) D B 1
B Z 分類	B Z 3

器具効率		6 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 6 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	4 2	3 5	3 0	2 7	4 1	3 4	3 0	2 7	4 0	3 4	3 0	2 7	3 8	3 3	2 9	2 7	2 5	
			0 . 7 7	0 . 8	4 9	4 2	3 8	3 5	4 8	4 2	3 8	3 5	4 6	4 1	3 7	3 5	4 5	4 0	3 7	3 4	3 3	
			0 . 6 8	1 . 0	5 3	4 7	4 3	4 0	5 2	4 7	4 3	4 0	5 1	4 6	4 3	4 0	4 9	4 5	4 2	4 0	3 8	
				1 . 2 5	5 7	5 2	4 8	4 5	5 6	5 1	4 8	4 5	5 4	5 0	4 7	4 5	5 3	4 9	4 7	4 4	4 3	
下方投影面積		c m ²	1 . 5	5 9	5 5	5 1	4 9	5 8	5 4	5 1	4 8	5 7	5 3	5 0	4 8	5 5	5 2	5 0	4 8	4 6		
等価発光面積		c m ²	2 . 0	6 2	5 9	5 6	5 3	6 1	5 8	5 5	5 3	6 0	5 7	5 5	5 2	5 8	5 6	5 4	5 2	5 1		
取付 高さ	器具間隔最大限		2 . 5	6 4	6 1	5 9	5 6	6 3	6 1	5 8	5 6	6 2	5 9	5 7	5 5	6 0	5 8	5 6	5 5	5 3		
	横方向 (A) 縦方向 (B)		3 . 0	6 5	6 3	6 1	5 9	6 5	6 2	6 0	5 8	6 3	6 1	5 9	5 7	6 1	6 0	5 8	5 7	5 5		
1 . 5m	2 . 3 3 m	1 . 9 3 m	4 . 0	6 7	6 5	6 3	6 2	6 6	6 4	6 3	6 1	6 5	6 3	6 2	6 0	6 3	6 2	6 0	5 9	5 8		
2	3 . 0 9	2 . 4	5 . 0	6 8	6 6	6 5	6 3	6 7	6 6	6 4	6 3	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	5 9		
2 . 5	3 . 8 5	2 . 8 8	7 . 0	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 5	6 4	6 4	6 3	6 1		
3	4 . 6	3 . 3 7	1 0 . 0	7 0	6 9	6 8	6 7	6 9	6 8	6 7	6 7	6 7	6 7	6 6	6 5	6 6	6 5	6 5	6 4	6 2		

