

屋内照明器具特性

品番 (品名)	XF X4 3 0 P L W	
光源	LED4000_85_2810 x1	2810.0 lm
管理番号	K0193346(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		下方光束 100%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.6	4.6	4.0	3.5	5.4	4.5	3.9	3.5	3.3	
	中	0.77	0.8	7.0	5.9	5.1	4.6	6.8	5.8	5.1	4.6	6.6	5.7	5.0	4.6	6.3	5.5	5.0	4.5	4.3	
	否	0.68	1.0	7.6	6.6	5.9	5.4	7.5	6.5	5.9	5.3	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.3	5.1	
			0.68	1.25	8.2	7.3	6.6	6.1	8.0	7.2	6.6	6.1	7.8	7.0	6.5	6.0	7.5	6.9	6.4	6.0	5.8
下方投影面積	cm ²		1.5	8.6	7.8	7.2	6.7	8.4	7.7	7.1	6.6	8.2	7.5	7.0	6.6	7.9	7.3	6.9	6.5	6.3	
等価発光面積	cm ²		2.0	9.1	8.5	7.9	7.5	9.0	8.4	7.9	7.4	8.7	8.2	7.7	7.3	8.4	8.0	7.6	7.3	7.0	
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.4	8.0	9.3	8.8	8.3	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.5	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.5	9.1	8.7	8.4	9.3	8.9	8.5	8.2	9.0	8.7	8.4	8.1	7.9	
1.5m	1.91m	2.11m	4.0	10.0	9.6	9.2	8.9	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.3	9.1	8.8	8.6	8.4	
2	2.52	2.66	5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.5	9.2	9.7	9.5	9.3	9.1	9.5	9.3	9.1	8.9	8.7	
2.5	3.14	3.24	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.7	9.6	9.4	9.3	9.0	
3	3.75	3.82	10.0	10.5	10.3	10.2	10.0	10.4	10.2	10.1	9.9	10.1	10.0	9.9	9.7	9.9	9.8	9.7	9.6	9.3	

