

屋内照明器具特性	
品番 (品名)	XF X4 3 0 RHW
光源	LED4000_85_2970 x1 2970.0 lm
管理番号	K0192152(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.7	4.5	3.7	3.1	5.5	4.4	3.6	3.1	5.3	4.3	3.6	3.1	5.1	4.2	3.6	3.1	2.9
	中	0.77	0.8	6.7	5.5	4.7	4.2	6.5	5.5	4.7	4.2	6.3	5.3	4.6	4.1	6.0	5.2	4.6	4.1	3.9
	否	0.68	1.0	7.3	6.3	5.5	4.9	7.2	6.2	5.5	4.9	6.9	6.0	5.4	4.9	6.6	5.9	5.3	4.8	4.6
			1.25	7.9	7.0	6.2	5.7	7.8	6.9	6.2	5.7	7.5	6.7	6.1	5.6	7.2	6.5	6.0	5.6	5.3
下方投影面積		cm ²	1.5	8.4	7.5	6.8	6.2	8.2	7.4	6.7	6.2	7.9	7.2	6.6	6.2	7.6	7.0	6.5	6.1	5.9
等価発光面積		cm ²	2.0	8.9	8.2	7.6	7.1	8.8	8.1	7.5	7.1	8.5	7.9	7.4	7.0	8.2	7.7	7.3	6.9	6.7
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.1	7.7	9.1	8.6	8.1	7.6	8.8	8.3	7.9	7.5	8.6	8.1	7.8	7.4	7.2
	横方向 (A)	縦方向 (B)	3.0	9.5	9.0	8.5	8.1	9.4	8.9	8.4	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.1	7.8	7.6
1.5m	1.99m	2.12m	4.0	9.9	9.4	9.0	8.7	9.7	9.3	9.0	8.6	9.4	9.1	8.8	8.5	9.2	8.9	8.6	8.4	8.1
2	2.62	2.66	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.9	9.4	9.1	8.9	8.7	8.5
2.5	3.26	3.22	7.0	10.3	10.0	9.8	9.5	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.1	8.9
3	3.89	3.8	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.6	9.8	9.7	9.6	9.5	9.2

