

屋内照明器具特性	
品番 (品名)	XF X4 3 0 S L W
光源	LED4000_85_2840 x1 2840.0 1 m
管理番号	K0193785 (0) DB 1
B Z 分類	B Z 4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.8	3.4	5.3	4.4	3.8	3.4	3.2
	中	0.77	0.8	6.9	5.8	5.0	4.4	6.7	5.7	5.0	4.4	6.5	5.5	4.9	4.4	6.2	5.4	4.8	4.4	4.2
	否	0.68	1.0	7.5	6.5	5.8	5.2	7.4	6.4	5.7	5.2	7.1	6.3	5.6	5.1	6.8	6.1	5.6	5.1	4.9
			1.25	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.9	7.6	6.9	6.3	5.9	7.4	6.7	6.2	5.8	5.6
下方投影面積		cm ²	1.5	8.5	7.7	7.0	6.5	8.3	7.6	6.9	6.4	8.0	7.4	6.8	6.4	7.8	7.2	6.7	6.3	6.1
等価発光面積		cm ²	2.0	9.0	8.3	7.8	7.3	8.9	8.2	7.7	7.2	8.6	8.0	7.6	7.2	8.3	7.8	7.4	7.1	6.8
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.4	8.0	7.7	8.6	8.2	7.9	7.6	7.3
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	9.0	8.5	8.2	9.2	8.7	8.4	8.1	8.9	8.5	8.2	8.0	7.7
1.5m	1.92 m	2.11 m	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2
2	2.54	2.66	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.5
2.5	3.15	3.22	7.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9
3	3.77	3.8	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

