

屋内照明器具特性

品番 (品名)	XF X4 3 0 TNN														
光源	LED5000_85_3030 x1 3030.0 lm														
管理番号	K0192145(0)D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 (X0.01)																ZCM	
下方光束	100 %																			
保守率	良 中 否	0.83	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.5	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8
		0.81	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.9	5.0	4.4	3.9	3.7
		0.77	1.0	7.2	6.1	5.3	4.7	7.1	6.0	5.3	4.7	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.6	4.4
			1.25	7.8	6.8	6.0	5.5	7.7	6.7	6.0	5.4	7.3	6.5	5.9	5.4	7.0	6.4	5.8	5.3	5.1
下方投影面積 等価発光面積	c m ²	1.5	8.2	7.3	6.6	6.0	8.1	7.2	6.5	6.0	7.7	7.0	6.4	5.9	7.4	6.8	6.3	5.9	5.6	
		2.0	8.8	8.0	7.4	6.8	8.6	7.9	7.3	6.8	8.3	7.7	7.2	6.7	8.0	7.5	7.0	6.6	6.4	
		2.5	9.2	8.5	7.9	7.4	9.0	8.4	7.8	7.4	8.7	8.1	7.7	7.3	8.4	7.9	7.5	7.2	6.9	
取付高さ	器具間隔最大限		3.0	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.5	8.0	7.7	8.6	8.2	7.9	7.6	7.3
	横方向 (A)	縦方向 (B)																		
1.5m	1.96 m	2.1 m	4.0	9.7	9.2	8.8	8.4	9.6	9.1	8.7	8.4	9.3	8.9	8.5	8.2	9.0	8.7	8.4	8.1	7.8
2	2.58	2.64	5.0	9.9	9.5	9.1	8.8	9.8	9.4	9.0	8.7	9.5	9.2	8.9	8.6	9.2	8.9	8.7	8.5	8.2
2.5	3.21	3.2	7.0	10.2	9.8	9.6	9.3	10.0	9.7	9.5	9.2	9.7	9.5	9.3	9.0	9.5	9.3	9.1	8.9	8.6
3	3.84	3.78	10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.7	9.5	9.4	9.2	8.9

