

屋内照明器具特性	
品番 (品名)	S L B 8 1 6 7 5
光源	LDA3 L - E17 / C / W ×1 280.0 l m
管理番号	K0157685 (0) DB 1
B Z 分類	B Z 7

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		34 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		55 %																					
保守率		良 中 否	0.63	0.6	42	31	23	19	39	29	22	18	33	25	20	16	28	22	17	14	10		
			0.6	0.8	49	38	31	26	46	36	29	24	39	32	26	22	34	27	23	19	14		
			0.56	1.0	55	44	37	31	51	42	35	30	44	36	31	26	37	31	27	23	17		
				1.25	60	50	43	37	56	47	40	35	48	41	36	31	41	35	31	27	21		
下方投影面積		cm ²	1.5	63	54	47	42	59	51	44	39	51	45	39	35	44	39	34	31	24			
等価発光面積			cm ²	2.0	68	60	54	49	64	57	51	46	55	50	45	41	48	43	39	36	28		
				2.5	71	64	59	54	67	61	55	51	58	53	49	45	50	46	43	40	31		
取付 高さ	器具間隔最大限		3.0	74	68	62	58	69	64	59	55	60	56	52	49	52	49	46	43	34			
	横方向 (A)		縦方向 (B)		4.0	77	72	67	63	72	68	63	60	63	60	56	53	55	52	49	47	37	
H m	0.93 H m	1.39 H m	5.0	79	74	70	67	74	70	67	63	65	62	59	56	57	54	52	50	39			
			7.0	81	78	75	72	76	73	70	68	67	65	63	60	59	57	55	53	43			
			10.0	83	80	78	76	78	76	74	72	69	67	66	64	61	59	58	56	45			

