

屋内照明器具特性	
品番 (品名)	S L B 8 1 8 8 9
光源	LED2700_70_930 ×1 930.0 l m
管理番号	K0192614 (0) DR 1
B Z 分類	B Z 7

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		31 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		69 %																						
保守率		良 中 否	0.67	0.6	47	34	26	20	44	33	25	20	39	29	22	18	34	26	20	16	12			
			0.63	0.8	56	43	35	28	52	41	33	27	46	36	30	25	40	32	26	22	17			
			0.56	1.0	62	50	41	34	58	47	39	33	51	42	35	30	44	37	31	27	21			
				1.25	67	56	47	41	63	53	45	39	55	47	41	35	48	42	36	32	25			
下方投影面積		cm ²	1.5	72	61	53	46	67	58	50	44	59	51	45	40	51	45	40	36	28				
等価発光面積		cm ²	2.0	77	68	60	54	73	64	57	51	64	57	51	47	56	51	46	42	34				
取付 高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	52	59	54	50	46	37				
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	65	60	55	62	57	53	50	41				
1.5m	2.12 m	1.95 m	4.0	87	81	75	71	82	77	72	67	73	69	65	61	65	61	58	55	45				
2	2.81	2.56	5.0	90	84	79	75	85	80	76	71	76	72	68	65	67	64	61	58	48				
2.5	3.52	3.18	7.0	92	88	84	81	88	84	80	77	79	75	72	70	70	67	65	63	52				
3	4.21	3.8	10.0	95	91	88	85	90	87	84	82	81	78	76	74	72	70	68	67	56				

