

屋内照明器具特性	
品番 (品名)	XF X4 3 0 WE V
光源	LED3500_85_2920 x1 2920.0 1 m
管理番号	K0192166 (0) DR 1
BZ分類	BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 6.0 / BZ6

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	10 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	90 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	5.4	4.1	3.4	2.8	5.2	4.0	3.3	2.8	4.9	3.9	3.2	2.7	4.5	3.7	3.1	2.6	2.4			
	中	0.81	0.8	6.3	5.1	4.3	3.7	6.1	5.0	4.3	3.7	5.7	4.8	4.1	3.6	5.4	4.6	4.0	3.5	3.2			
	否	0.77	1.0	7.0	5.8	5.0	4.4	6.7	5.7	4.9	4.4	6.3	5.4	4.8	4.2	5.9	5.2	4.6	4.1	3.8			
			1.25	7.5	6.5	5.7	5.1	7.3	6.3	5.6	5.0	6.8	6.0	5.4	4.9	6.4	5.7	5.2	4.8	4.4			
下方投影面積		cm ²	1.5	7.9	7.0	6.2	5.7	7.7	6.8	6.1	5.6	7.2	6.5	5.9	5.4	6.8	6.2	5.6	5.2	4.8			
等価発光面積		cm ²	2.0	8.5	7.7	7.0	6.5	8.2	7.5	6.9	6.3	7.7	7.1	6.6	6.1	7.3	6.8	6.3	5.9	5.5			
取付高さ	器具間隔最大限		2.5	8.9	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.1	7.5	7.1	6.7	7.6	7.2	6.8	6.4	6.0			
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.4	8.8	8.3	7.8	7.3	8.3	7.9	7.4	7.1	7.9	7.5	7.1	6.8	6.3			
1.5m	1.94 m	2.1 m	4.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.7	8.3	7.9	7.6	8.2	7.9	7.6	7.3	6.8			
2	2.57	2.64	5.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	8.9	8.6	8.2	8.0	8.4	8.1	7.9	7.7	7.1			
2.5	3.19	3.2	7.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.1	8.9	8.6	8.4	8.7	8.5	8.3	8.1	7.5			
3	3.81	3.78	10.0	10.1	9.8	9.6	9.3	9.8	9.6	9.4	9.2	9.4	9.2	9.0	8.8	8.9	8.7	8.6	8.4	7.9			

