

屋内照明器具特性	
品番 (品名)	S L B 1 9 2 8 1 B
光源	L D A 7 L - D - G / S / Z 6 × 1 8 1 0 . 0 l m
管理番号	K 0 1 2 6 4 8 1 (0) D B 1
B Z 分類	B Z 8

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		4 2 %	室指数	照明率 (X 0 . 0 1)																	Z C M		
下方光束		4 7 %																					
保守率		良 中 否	0 . 6 3	0 . 6	4 0	2 9	2 2	1 7	3 7	2 7	2 0	1 6	3 1	2 3	1 7	1 4	2 5	1 9	1 4	1 1	7		
			0 . 6	0 . 8	4 8	3 7	2 9	2 4	4 4	3 4	2 7	2 2	3 6	2 9	2 3	1 9	3 0	2 4	1 9	1 6	1 0		
			0 . 5 6	1 . 0	5 3	4 2	3 5	2 9	4 9	3 9	3 2	2 7	4 0	3 3	2 7	2 3	3 3	2 7	2 3	1 9	1 3		
				1 . 2 5	5 8	4 8	4 0	3 5	5 3	4 4	3 8	3 2	4 4	3 7	3 2	2 8	3 6	3 1	2 7	2 3	1 5		
下方投影面積		c m ²	1 . 5	6 1	5 2	4 5	3 9	5 6	4 8	4 2	3 7	4 7	4 1	3 6	3 1	3 9	3 4	3 0	2 6	1 8			
等価発光面積		c m ²	2 . 0	6 6	5 8	5 2	4 6	6 1	5 4	4 8	4 3	5 1	4 6	4 1	3 7	4 2	3 8	3 4	3 1	2 1			
取付 高さ	器具間隔最大限		2 . 5	7 0	6 2	5 6	5 1	6 4	5 8	5 2	4 8	5 4	4 9	4 5	4 1	4 5	4 1	3 7	3 4	2 4			
	横方向 (A)	縦方向 (B)	3 . 0	7 2	6 6	6 0	5 5	6 7	6 1	5 6	5 1	5 6	5 2	4 8	4 4	4 7	4 3	4 0	3 7	2 6			
H m	1 . 5 9 H m	1 . 5 9 H m	4 . 0	7 5	7 0	6 5	6 1	7 0	6 5	6 1	5 7	5 9	5 5	5 2	4 9	4 9	4 6	4 4	4 1	2 9			
			5 . 0	7 7	7 2	6 8	6 4	7 2	6 7	6 4	6 0	6 1	5 8	5 5	5 2	5 1	4 8	4 6	4 4	3 2			
			7 . 0	8 0	7 6	7 3	6 9	7 4	7 1	6 8	6 5	6 3	6 1	5 8	5 6	5 3	5 1	4 9	4 8	3 5			
			1 0 . 0	8 2	7 9	7 6	7 4	7 6	7 3	7 1	6 9	6 5	6 3	6 1	6 0	5 5	5 4	5 2	5 1	3 7			

