

屋内照明器具特性	
品番 (品名)	XAD3200L
光源	LLD4000LCS1 ×1 830.0 lm
管理番号	K0181859 (0) DR1
BZ分類	BZ4/0.9/BZ3

器具効率		83 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z C M
保守率		良 中 否	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29				
			0.63	0.8	59	50	45	40	58	50	44	40	56	49	44	40	54	48	43	40	38				
			0.56	1.0	65	57	51	47	63	56	51	47	61	55	50	46	59	54	50	46	45				
				1.25	69	62	57	53	68	62	57	53	66	60	56	53	64	59	55	52	50				
下方投影面積		cm ²		1.5	73	66	62	58	71	66	61	57	69	64	60	57	67	63	59	56	55				
			等価発光面積	cm ²	2.0	77	72	68	64	76	71	67	64	73	69	66	63	71	68	65	62	61			
取付 高さ	器具間隔最大限			2.5	80	75	72	68	78	74	71	68	76	73	70	67	74	71	69	66	65				
	横方向 (A) 縦方向 (B)			3.0	81	78	74	72	80	77	74	71	78	75	72	70	76	73	71	69	67				
H m	1.26 H m 1.26 H m			4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71				
				5.0	85	82	80	78	84	81	79	78	82	80	78	76	80	78	77	75	73				
				7.0	86	85	83	81	85	84	82	81	83	82	81	79	81	80	79	78	76				
				10.0	87	86	85	84	86	85	84	83	84	83	82	82	82	82	81	80	78				

