

屋内照明器具特性

品番 (品名)	XF X4 3 4 F H W	
光源	LED4000_85_1920 x1	1920.0 1 m
管理番号	K0192930 (0) DB 1	
BZ分類	BZ2	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	100 %		室指数	照明率 (X0.01)																			
保守率	良	0.81	0.6	6.9	5.9	5.3	4.9	6.7	5.8	5.3	4.9	6.6	5.8	5.2	4.8	6.4	5.7	5.2	4.8	4.7			
	中	0.77	0.8	7.8	7.0	6.4	6.0	7.7	6.9	6.4	6.0	7.5	6.8	6.3	5.9	7.3	6.7	6.2	5.9	5.7			
	否	0.68	1.0	8.4	7.7	7.1	6.7	8.3	7.6	7.1	6.7	8.1	7.5	7.0	6.7	7.9	7.3	6.9	6.6	6.4			
			1.25	8.9	8.2	7.7	7.4	8.8	8.2	7.7	7.3	8.6	8.0	7.6	7.3	8.3	7.9	7.5	7.2	7.1			
下方投影面積	c m ²		1.5	9.2	8.6	8.2	7.8	9.1	8.6	8.1	7.8	8.9	8.4	8.0	7.7	8.6	8.3	7.9	7.7	7.5			
			2.0	9.6	9.2	8.8	8.4	9.5	9.1	8.7	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.5	8.2	8.0			
取付高さ	器具間隔最大限		2.5	9.9	9.5	9.1	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.3	9.0	8.8	8.6	8.4			
	横方向 (A)	縦方向 (B)	3.0	10.0	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.2	9.0	9.5	9.2	9.0	8.9	8.6			
1.5m	1.8 m	1.89 m	4.0	10.3	10.0	9.7	9.5	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.7	9.5	9.3	9.2	8.9			
2	2.38	2.34	5.0	10.4	10.1	9.9	9.8	10.2	10.0	9.9	9.7	10.0	9.8	9.7	9.5	9.8	9.6	9.5	9.4	9.1			
2.5	2.97	2.81	7.0	10.5	10.3	10.2	10.1	10.4	10.2	10.1	10.0	10.2	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.4			
3	3.55	3.3	10.0	10.6	10.5	10.4	10.3	10.5	10.4	10.3	10.2	10.3	10.2	10.1	10.0	10.0	9.9	9.8	9.5	9.5			

