

屋内照明器具特性	
品番 (品名)	S L B 5 0 6 6 9
光源	LED3500_70_2100 ×1 2100.0 lm
管理番号	K0192395 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	55	43	35	30	53	42	35	30	50	40	34	29	47	39	33	28	26
			0.63	0.8	65	53	46	40	63	52	45	39	59	50	43	38	55	48	42	37	34
			0.56	1.0	71	60	53	47	69	59	52	46	65	56	50	45	61	54	48	44	41
				1.25	77	67	60	54	75	66	59	53	70	62	57	52	66	60	54	50	47
下方投影面積		cm ²		1.5	81	72	65	59	78	70	64	58	74	67	61	57	70	64	59	55	51
			等価発光面積	cm ²	2.0	86	79	72	67	84	77	71	66	79	73	68	64	75	70	66	62
取付 高さ	器具間隔最大限			2.5	90	83	78	73	87	81	76	72	82	77	73	69	78	74	70	67	62
	横方向 (A) 縦方向 (B)			3.0	92	86	81	77	90	84	80	76	85	80	76	73	80	77	73	70	66
1.5m	1.9 m	2.14 m		4.0	95	91	86	83	93	88	85	81	88	84	81	78	84	81	78	75	70
2	2.51	2.7		5.0	97	93	90	86	95	91	88	85	90	87	84	82	86	83	81	79	73
2.5	3.12	3.27		7.0	100	96	94	91	97	94	92	89	92	90	88	86	88	86	84	83	77
3	3.72	3.87		10.0	101	99	97	95	99	97	95	93	94	93	91	89	90	88	87	86	80

