

屋内照明器具特性	
品番 (品名)	S L B 5 0 6 7 3
光源	LED5000_70_1480 ×1 1480.0 lm
管理番号	K0192394 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		15 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		85 %																								
保守率		良 中 否	0.69	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20					
			0.67	0.8	61	49	40	34	59	47	39	34	54	44	38	32	50	42	36	31	28					
			0.63	1.0	67	56	47	41	65	54	46	40	60	51	44	39	55	47	42	37	33					
				1.25	73	62	54	48	70	60	53	47	65	57	50	45	60	53	48	43	39					
下方投影面積		cm ²	1.5	77	67	60	53	74	65	58	52	69	61	55	50	64	57	52	48	43						
等価発光面積		cm ²	2.0	83	74	67	61	80	72	66	60	74	68	62	57	69	63	59	55	50						
取付 高さ	器具間隔最大限		2.5	87	79	73	67	83	77	71	66	78	72	67	63	72	67	63	60	54						
	横方向 (A)		縦方向 (B)	3.0	89	82	77	72	86	80	75	70	80	75	71	67	75	71	67	64	58					
1.5m	2.05 m	1.94 m	4.0	93	87	82	78	89	84	80	76	84	79	76	72	78	75	72	69	63						
2	2.74	2.56	5.0	95	90	86	82	92	87	84	80	86	82	79	76	80	77	75	72	66						
2.5	3.44	3.18	7.0	97	94	90	87	94	91	88	85	89	86	83	81	83	81	79	77	70						
3	4.12	3.81	10.0	99	97	94	92	96	94	92	89	91	89	87	85	85	84	82	80	74						

