

屋内照明器具特性	
品番 (品名)	S L B 5 0 6 8 2
光源	LED5000_70_3620 ×1 3620.0 lm
管理番号	K0192393 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		15 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		85 %																							
保守率		良 中 否	0.69	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	34	28	23	20				
			0.67	0.8	61	49	40	34	59	47	40	34	54	45	38	32	50	42	36	31	28				
			0.63	1.0	67	56	47	41	65	54	46	40	60	51	44	39	55	48	42	37	33				
				1.25	73	62	54	48	70	60	53	47	65	57	50	45	60	53	48	43	39				
下方投影面積		cm ²	1.5	77	67	60	53	74	65	58	52	69	61	55	50	64	57	52	48	43					
			2.0	83	74	67	62	80	72	66	60	74	68	62	58	69	64	59	55	50					
取付 高さ	器具間隔最大限		2.5	87	79	73	67	84	77	71	66	78	72	67	63	72	68	64	60	54					
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	86	80	75	70	80	75	71	67	75	71	67	64	58					
5 m	6.82 m	6.44 m	4.0	93	87	82	78	90	85	80	76	84	80	76	73	78	75	72	69	63					
7	9.6	8.96	5.0	95	90	86	82	92	88	84	80	86	82	79	76	81	78	75	73	66					
10	13.7	12.8	7.0	97	94	90	87	94	91	88	85	89	86	83	81	83	81	79	77	70					
15	20.56	19.2	10.0	99	97	94	92	96	94	92	89	91	89	87	85	86	84	82	81	74					

