

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | S L B 5 5 0 1 3              |
| 光源       | LED3500_70_3395 ×1 3395.0 lm |
| 管理番号     | K0195204 ( 0 ) DB 1          |
| B Z 分類   | B Z 6                        |

| 器具効率     |           | 100 %           | 反射率       | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |   |
|----------|-----------|-----------------|-----------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|---|
|          |           |                 |           | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |   |
|          |           |                 |           | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |   |
| 上方光束     |           | 20 %            | 室指数       | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C | M |
| 下方光束     |           | 80 %            |           |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |   |
| 保守率      |           | 良<br>中<br>否     | 0.69      | 0.6           | 51   | 39 | 31 | 25 | 49   | 37 | 30 | 25 | 44   | 35 | 28 | 23 | 40   | 32 | 26 | 22 | 19  |  |   |   |   |
|          |           |                 | 0.67      | 0.8           | 61   | 49 | 40 | 34 | 58   | 47 | 39 | 34 | 53   | 43 | 37 | 32 | 48   | 40 | 35 | 30 | 26  |  |   |   |   |
|          |           |                 | 0.63      | 1.0           | 67   | 56 | 47 | 41 | 64   | 54 | 46 | 40 | 58   | 50 | 43 | 38 | 53   | 46 | 40 | 36 | 32  |  |   |   |   |
|          |           |                 |           | 1.25          | 73   | 62 | 54 | 48 | 70   | 60 | 53 | 47 | 64   | 56 | 49 | 45 | 58   | 52 | 46 | 42 | 37  |  |   |   |   |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5       | 77            | 67   | 60 | 54 | 74 | 65   | 58 | 52 | 67 | 60   | 54 | 49 | 62 | 56   | 51 | 47 | 41 |     |  |   |   |   |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0       | 83            | 74   | 68 | 62 | 79 | 72   | 65 | 60 | 73 | 66   | 61 | 57 | 67 | 62   | 57 | 54 | 48 |     |  |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5       | 86            | 79   | 73 | 68 | 83 | 76   | 71 | 66 | 76 | 71   | 66 | 62 | 70 | 66   | 62 | 58 | 52 |     |  |   |   |   |
|          | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0           | 89   | 82 | 77 | 72 | 85   | 80 | 75 | 70 | 79   | 74 | 70 | 66 | 72   | 69 | 65 | 62 | 55  |  |   |   |   |
| 1.5m     | 2.28 m    | 2.29 m          | 4.0       | 92            | 87   | 82 | 78 | 89 | 84   | 80 | 76 | 82 | 78   | 75 | 71 | 76 | 73   | 70 | 67 | 60 |     |  |   |   |   |
| 2        | 2.98      | 2.83            | 5.0       | 94            | 90   | 86 | 82 | 91 | 87   | 83 | 80 | 84 | 81   | 78 | 75 | 78 | 75   | 73 | 70 | 63 |     |  |   |   |   |
| 2.5      | 3.7       | 3.41            | 7.0       | 97            | 93   | 90 | 87 | 93 | 90   | 87 | 85 | 87 | 84   | 82 | 80 | 80 | 78   | 76 | 75 | 67 |     |  |   |   |   |
| 3        | 4.43      | 4               | 10.0      | 99            | 96   | 94 | 92 | 95 | 93   | 91 | 89 | 89 | 87   | 85 | 83 | 82 | 81   | 79 | 78 | 70 |     |  |   |   |   |

