

屋内照明器具特性	
品番 (品名)	S L B 5 5 0 1 9
光源	LED3500_70_1355 ×1 1355.0 lm
管理番号	K0195204 (0) DB 1
B Z 分類	B Z 6

器具効率		100 % 上方光束 20 % 下方光束 80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.69	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19	
			0.67	0.8	61	49	40	34	58	47	39	34	53	43	37	32	48	40	35	30	26	
			0.63	1.0	67	56	47	41	64	54	46	40	58	50	43	38	53	46	40	36	32	
			0.63	1.25	73	62	54	48	70	60	53	47	64	56	49	45	58	52	46	42	37	
下方投影面積		cm ²	1.5	77	67	60	54	74	65	58	52	67	60	54	49	62	56	51	47	41		
等価発光面積			cm ²	2.0	83	74	68	62	79	72	65	60	73	66	61	57	67	62	57	54	48	
				2.5	86	79	73	68	83	76	71	66	76	71	66	62	70	66	62	58	52	
取付 高さ	器具間隔最大限		3.0	89	82	77	72	85	80	75	70	79	74	70	66	72	69	65	62	55		
	横方向 (A)			縦方向 (B)		4.0	92	87	82	78	89	84	80	76	82	78	75	71	76	73	70	67
1.5m	2.2 m	1.96 m	5.0	94	90		86	82	91	87	83	80	84	81	78	75	78	75	73	70	63	
2	2.93	2.59		7.0	97		93	90	87	93	90	87	85	87	84	82	80	80	78	76	75	67
2.5	3.67	3.21			10.0		99	96	94	92	95	93	91	89	89	87	85	83	82	81	79	78
3	4.4	3.85																				

