

屋内照明器具特性	
品番 (品名)	S L B 5 5 0 2 4
光源	LED5000_70_2790 ×1 2790.0 lm
管理番号	K0195204 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.69	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19
			0.67	0.8	61	49	40	34	58	47	39	34	53	43	37	32	48	40	35	30	26
			1.0	67	56	47	41	64	54	46	40	58	50	43	38	53	46	40	36	32	
			0.63	1.25	73	62	54	48	70	60	53	47	64	56	49	45	58	52	46	42	37
下方投影面積		cm ²	1.5	77	67	60	54	74	65	58	52	67	60	54	49	62	56	51	47	41	
			等価発光面積		cm ²	2.0	83	74	68	62	79	72	65	60	73	66	61	57	67	62	57
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	76	71	66	76	71	66	62	70	66	62	58	52	
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	80	75	70	79	74	70	66	72	69	65	62	55	
1.5m	2.25 m	2.15 m	4.0	92	87	82	78	89	84	80	76	82	78	75	71	76	73	70	67	60	
2	2.96	2.73	5.0	94	90	86	82	91	87	83	80	84	81	78	75	78	75	73	70	63	
2.5	3.69	3.32	7.0	97	93	90	87	93	90	87	85	87	84	82	80	80	78	76	75	67	
3	4.4	3.92	10.0	99	96	94	92	95	93	91	89	89	87	85	83	82	81	79	78	70	

