

屋内照明器具特性	
品番 (品名)	XAD3460V
光源	LLD3020VCB1 ×1 795.0 lm
管理番号	K0175559 (0) DR1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		88 %																						
保守率		良 中 否	0.67	0.6	73	67	63	61	72	67	63	61	71	66	63	61	70	66	63	61	60			
			0.63	0.8	78	73	69	67	77	72	69	67	76	72	69	66	74	71	68	66	65			
			0.56	1.0	81	76	73	71	80	76	73	71	79	75	72	70	77	74	72	70	69			
				1.25	84	80	77	74	83	79	76	74	81	78	76	74	80	77	75	73	72			
下方投影面積		c m ²		1.5	86	82	79	77	85	81	79	77	83	80	78	76	81	79	77	75	74			
等価発光面積			c m ²	2.0	88	85	83	80	87	84	82	80	85	83	81	79	84	82	80	79	77			
取付 高さ	器具間隔最大限		2.5	89	87	85	83	88	86	84	82	87	85	83	82	85	83	82	81	79				
	横方向 (A)		縦方向 (B)	3.0	90	88	86	85	89	87	86	84	88	86	84	83	86	84	83	82	80			
H m	0.41 H m	0.41 H m	4.0	92	90	88	87	91	89	88	86	89	87	86	85	87	86	85	84	82				
			5.0	92	91	90	88	91	90	89	88	89	88	87	86	88	87	86	85	83				
			7.0	93	92	91	90	92	91	90	89	90	89	89	88	88	88	87	87	84				
			10.0	94	93	92	92	93	92	91	91	91	90	90	89	89	89	88	88	85				

