

屋内照明器具特性	
品番 (品名)	XAD5100L
光源	LLD5000LCC1 ×1 1140.0lm
管理番号	K0187672 (1) DR1
BZ分類	BZ3/0.7/BZ2

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	62	53	47	42	61	52	47	42	60	52	46	42	58	51	46	42	41
			0.63	0.8	72	64	58	54	71	63	57	53	69	62	57	53	67	61	56	53	51
			0.56	1.0	78	71	65	61	77	70	65	61	75	69	64	61	73	67	63	60	58
				1.25	83	77	72	68	82	76	71	67	80	74	70	67	78	73	69	67	65
下方投影面積		cm ²		1.5	86	81	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69
			等価発光面積		cm ²	2.0	91	86	82	79	89	85	81	78	87	83	80	77	85	82	79
取付	器具間隔最大限			2.5	93	89	86	83	92	88	85	82	89	86	84	81	87	85	82	80	78
高さ	横方向 (A)		縦方向 (B)	3.0	95	91	88	86	93	90	88	85	91	88	86	84	89	87	85	83	81
H m	1.24 H m		1.24 H m	4.0	97	94	92	89	96	93	91	89	93	91	89	88	91	89	88	86	84
				5.0	98	96	94	92	97	95	93	91	94	93	91	90	92	91	90	88	86
				7.0	99	98	96	95	98	97	95	94	96	95	93	92	94	93	92	91	88
				10.0	100	99	98	97	99	98	97	96	97	96	95	94	95	94	93	93	90

