

屋内照明器具特性	
品番 (品名)	S L B 5 5 1 0 8
光源	LED2700_70_915 ×1 915.0 l m
管理番号	K0195370 (0) DR 1
B Z 分類	B Z 1 0

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z CM
保守率		良 中 否	0.69	0.6	42	29	21	15	38	27	19	14	31	21	15	11	24	17	12	8	3				
			0.67	0.8	50	37	28	22	45	34	26	20	36	27	21	16	28	21	16	12	5				
			0.63	1.0	56	43	34	28	51	39	31	25	41	32	25	20	32	25	20	16	7				
			1.25	61	50	41	34	56	45	37	31	45	37	30	25	35	29	24	19	10					
下方投影面積		cm ²	1.5	66	54	46	39	60	50	42	36	48	41	34	29	38	32	27	23	12					
等価発光面積			2.0	71	62	53	47	65	56	49	43	53	46	40	36	42	37	32	28	16					
取付高さ	器具間隔最大限			2.5	75	66	59	53	69	61	54	48	56	50	45	40	45	40	36	32	20				
	横方向 (A)		縦方向 (B)	3.0	78	70	63	57	71	64	58	53	59	53	48	44	47	43	39	36	22				
1.5m	0	m	1.93	m	4.0	82	75	69	64	75	69	64	59	62	58	53	49	50	47	43	40	26			
2	0		2.33		5.0	84	78	73	68	77	72	68	63	65	61	57	53	52	49	46	44	29			
2.5	0		2.75		7.0	87	83	78	74	80	76	73	69	67	64	61	58	55	53	50	48	32			
3	0		3.22		10.0	90	86	83	80	83	80	77	74	70	67	65	63	58	56	54	52	36			

