

屋内照明器具特性

品番 (品名)	XF X4 3 7 GHV									
光源	LED3500_85_2970 x1 2970.0 lm									
管理番号	K0192146(0)D 1									
BZ分類	BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	反射率	10%				10%				10%				10%				0%			
下方光束	100%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM		
保守率	良 中 否	0.81	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.6	4.6	4.0	3.5	5.4	4.5	3.9	3.5	3.3		
		0.77	0.8	7.0	5.9	5.2	4.7	6.8	5.8	5.1	4.6	6.6	5.7	5.1	4.6	6.4	5.6	5.0	4.6	4.4		
		0.68	1.0	7.7	6.7	6.0	5.5	7.5	6.6	6.0	5.4	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.2		
			1.25	8.3	7.4	6.8	6.2	8.1	7.3	6.7	6.2	7.8	7.1	6.6	6.2	7.6	7.0	6.5	6.1	5.9		
下方投影面積		cm ²																				
等価発光面積		cm ²																				
取付高さ	器具間隔最大限		2.5																			
	横方向 (A)	縦方向 (B)		3.0																		
1.5m	1.9m	2.12m	4.0																			
2	2.52	2.66	5.0																			
2.5	3.13	3.23	7.0																			
3	3.74	3.81	10.0																			

