

屋内照明器具特性	
品番 (品名)	S L B 5 5 2 0 4
光源	LED3500_70_955 ×1 955.0 l m
管理番号	K0195206 (0) DB 1
B Z 分類	B Z 1 0

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		4 9 %																							
保守率		良 中 否	0 . 6 9	0 . 6	4 2	2 9	2 1	1 5	3 8	2 7	1 9	1 4	3 1	2 2	1 5	1 1	2 4	1 7	1 2	8	3				
			0 . 6 7	0 . 8	5 0	3 7	2 8	2 2	4 5	3 4	2 6	2 0	3 7	2 8	2 1	1 6	2 9	2 1	1 6	1 2	5				
			0 . 6 3	1 . 0	5 6	4 3	3 4	2 8	5 1	4 0	3 1	2 5	4 1	3 2	2 6	2 0	3 2	2 5	2 0	1 6	8				
				1 . 2 5	6 2	5 0	4 1	3 4	5 6	4 5	3 7	3 1	4 5	3 7	3 0	2 5	3 5	2 9	2 4	2 0	1 0				
下方投影面積		c m ²	1 . 5	6 6	5 5	4 6	3 9	6 0	5 0	4 2	3 6	4 9	4 1	3 5	2 9	3 8	3 2	2 7	2 3	1 3					
等価発光面積		c m ²	2 . 0	7 2	6 2	5 4	4 7	6 5	5 6	4 9	4 3	5 3	4 7	4 1	3 6	4 2	3 7	3 3	2 9	1 7					
取付 高さ	器具間隔最大限		2 . 5	7 5	6 7	5 9	5 3	6 9	6 1	5 4	4 9	5 7	5 1	4 5	4 1	4 5	4 1	3 6	3 3	2 0					
	横方向 (A)	縦方向 (B)	3 . 0	7 8	7 0	6 3	5 7	7 2	6 5	5 8	5 3	5 9	5 4	4 9	4 4	4 8	4 3	3 9	3 6	2 3					
1 . 5m	0	2 . 1 1	4 . 0	8 2	7 5	6 9	6 4	7 5	6 9	6 4	5 9	6 3	5 8	5 4	5 0	5 1	4 7	4 4	4 1	2 7					
2	0	2 . 7 4	5 . 0	8 4	7 9	7 3	6 9	7 8	7 3	6 8	6 4	6 5	6 1	5 7	5 4	5 3	5 0	4 7	4 4	2 9					
2 . 5	0	3 . 3 9	7 . 0	8 7	8 3	7 9	7 5	8 1	7 7	7 3	6 9	6 8	6 5	6 2	5 9	5 6	5 3	5 1	4 8	3 3					
3	0	4 . 0 5	1 0 . 0	9 0	8 6	8 3	8 0	8 3	8 0	7 7	7 4	7 0	6 8	6 5	6 3	5 8	5 6	5 4	5 2	3 6					

