

屋内照明器具特性	
品番 (品名)	S L B 5 5 2 0 5
光源	LED2700_70_870 ×1 870.0 l m
管理番号	K0195206 (0) DB 1
B Z 分類	B Z 1 0

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																	Z CM
保守率		良 中 否	0.69	0.6	42	29	21	15	38	27	19	14	31	22	15	11	24	17	12	8	3	
			0.67	0.8	50	37	28	22	45	34	26	20	37	28	21	16	29	21	16	12	5	
			0.63	1.0	56	43	34	28	51	40	31	25	41	32	26	20	32	25	20	16	8	
			1.25	62	50	41	34	56	45	37	31	45	37	30	25	35	29	24	20	10		
下方投影面積		cm ²	1.5	66	55	46	39	60	50	42	36	49	41	35	29	38	32	27	23	13		
等価発光面積			2.0	72	62	54	47	65	56	49	43	53	47	41	36	42	37	33	29	17		
取付	器具間隔最大限			2.5	75	67	59	53	69	61	54	49	57	51	45	41	45	41	36	33	20	
高さ	横方向 (A)		縦方向 (B)	3.0	78	70	63	57	72	65	58	53	59	54	49	44	48	43	39	36	23	
1.5m	0	m	2.11	m	4.0	82	75	69	64	75	69	64	59	63	58	54	50	51	47	44	41	27
2	0		2.74		5.0	84	79	73	69	78	73	68	64	65	61	57	54	53	50	47	44	29
2.5	0		3.39		7.0	87	83	79	75	81	77	73	69	68	65	62	59	56	53	51	48	33
3	0		4.05		10.0	90	86	83	80	83	80	77	74	70	68	65	63	58	56	54	52	36

