

屋内照明器具特性	
品番 (品名)	S L B 5 5 2 1 2
光源	LED5000_70_2445 ×1 2445.0 lm
管理番号	K0195206 (0) DB 1
B Z 分類	BZ10

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		4 9 %																					
保守率		良 中 否	0 . 6 9	0 . 6	4 2	2 9	2 1	1 5	3 8	2 7	1 9	1 4	3 1	2 2	1 5	1 1	2 4	1 7	1 2	8	3		
			0 . 6 7	0 . 8	5 0	3 7	2 8	2 2	4 5	3 4	2 6	2 0	3 7	2 8	2 1	1 6	2 9	2 1	1 6	1 2	5		
			0 . 6 3	1 . 0	5 6	4 3	3 4	2 8	5 1	4 0	3 1	2 5	4 1	3 2	2 6	2 0	3 2	2 5	2 0	1 6	8		
				1 . 2 5	6 2	5 0	4 1	3 4	5 6	4 5	3 7	3 1	4 5	3 7	3 0	2 5	3 5	2 9	2 4	2 0	1 0		
下方投影面積		c m ²	1 . 5	6 6	5 5	4 6	3 9	6 0	5 0	4 2	3 6	4 9	4 1	3 5	2 9	3 8	3 2	2 7	2 3	1 3			
			等価発光面積		c m ²	2 . 0	7 2	6 2	5 4	4 7	6 5	5 6	4 9	4 3	5 3	4 7	4 1	3 6	4 2	3 7	3 3	2 9	1 7
取付 高さ	器具間隔最大限		2 . 5	7 5	6 7	5 9	5 3	6 9	6 1	5 4	4 9	5 7	5 1	4 5	4 1	4 5	4 1	3 6	3 3	2 0			
	横方向 (A)	縦方向 (B)	3 . 0	7 8	7 0	6 3	5 7	7 2	6 5	5 8	5 3	5 9	5 4	4 9	4 4	4 8	4 3	3 9	3 6	2 3			
1 . 5m	0 m	2 . 3 9 m	4 . 0	8 2	7 5	6 9	6 4	7 5	6 9	6 4	5 9	6 3	5 8	5 4	5 0	5 1	4 7	4 4	4 1	2 7			
2	0	2 . 9 4	5 . 0	8 4	7 9	7 3	6 9	7 8	7 3	6 8	6 4	6 5	6 1	5 7	5 4	5 3	5 0	4 7	4 4	2 9			
2 . 5	0	3 . 5 8	7 . 0	8 7	8 3	7 9	7 5	8 1	7 7	7 3	6 9	6 8	6 5	6 2	5 9	5 6	5 3	5 1	4 8	3 3			
3	0	4 . 2 8	1 0 . 0	9 0	8 6	8 3	8 0	8 3	8 0	7 7	7 4	7 0	6 8	6 5	6 3	5 8	5 6	5 4	5 2	3 6			

