

# 屋内照明器具特性

|         |                        |  |  |  |  |
|---------|------------------------|--|--|--|--|
| 品番 (品名) | XAS 3 5 0 3            |  |  |  |  |
| 光源      | LLD3000CU1 x1 795.0 lm |  |  |  |  |
| 管理番号    | K0178926(0)DR1         |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ3            |  |  |  |  |

|        |                   |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 73%               | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束              |          | 0%               | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        | 下方光束              |          | 73%              |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |
| 室指数    | 照明率 ( X0.01 ) ZCM |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良                 | 0.67     | 0.6              | 4.4 | 3.6 | 3.1 | 2.7 | 4.4 | 3.6 | 3.1 | 2.7 | 4.2 | 3.5 | 3.0 | 2.7 | 4.0 | 3.4 | 3.0 | 2.7 | 2.6 |     |
|        | 中                 | 0.63     | 0.8              | 5.2 | 4.4 | 3.9 | 3.6 | 5.1 | 4.4 | 3.9 | 3.6 | 4.9 | 4.3 | 3.9 | 3.5 | 4.8 | 4.2 | 3.8 | 3.5 | 3.4 |     |
|        | 否                 | 0.56     | 1.0              | 5.7 | 5.0 | 4.5 | 4.2 | 5.6 | 5.0 | 4.5 | 4.1 | 5.4 | 4.8 | 4.4 | 4.1 | 5.2 | 4.7 | 4.4 | 4.1 | 3.9 |     |
|        |                   |          | 1.25             | 6.1 | 5.5 | 5.1 | 4.7 | 6.0 | 5.5 | 5.0 | 4.7 | 5.8 | 5.3 | 5.0 | 4.7 | 5.6 | 5.2 | 4.9 | 4.6 | 4.5 |     |
| 下方投影面積 | c m <sup>2</sup>  |          | 1.5              | 6.4 | 5.9 | 5.5 | 5.1 | 6.3 | 5.8 | 5.4 | 5.1 | 6.1 | 5.7 | 5.3 | 5.1 | 5.9 | 5.6 | 5.3 | 5.0 | 4.9 |     |
|        | 等価発光面積            |          | c m <sup>2</sup> | 2.0 | 6.8 | 6.4 | 6.0 | 5.7 | 6.7 | 6.3 | 5.9 | 5.7 | 6.5 | 6.1 | 5.9 | 5.6 | 6.3 | 6.0 | 5.8 | 5.6 | 5.4 |
| 取付高さ   | 器具間隔最大限           |          | 2.5              | 7.0 | 6.6 | 6.3 | 6.1 | 6.9 | 6.6 | 6.3 | 6.0 | 6.7 | 6.4 | 6.2 | 6.0 | 6.5 | 6.3 | 6.1 | 5.9 | 5.7 |     |
|        | 横方向 (A)           | 縦方向 (B)  | 3.0              | 7.2 | 6.9 | 6.6 | 6.3 | 7.1 | 6.8 | 6.5 | 6.3 | 6.9 | 6.6 | 6.4 | 6.2 | 6.7 | 6.5 | 6.3 | 6.1 | 6.0 |     |
| H m    | 1.23 H m          | 1.23 H m | 4.0              | 7.4 | 7.1 | 6.9 | 6.7 | 7.3 | 7.0 | 6.8 | 6.6 | 7.1 | 6.9 | 6.7 | 6.6 | 6.9 | 6.7 | 6.6 | 6.5 | 6.3 |     |
|        |                   |          | 5.0              | 7.5 | 7.3 | 7.1 | 6.9 | 7.4 | 7.2 | 7.0 | 6.9 | 7.2 | 7.0 | 6.9 | 6.8 | 7.0 | 6.9 | 6.8 | 6.7 | 6.5 |     |
|        |                   |          | 7.0              | 7.6 | 7.4 | 7.3 | 7.2 | 7.5 | 7.4 | 7.2 | 7.1 | 7.3 | 7.2 | 7.1 | 7.0 | 7.1 | 7.1 | 7.0 | 6.9 | 6.7 |     |
|        |                   |          | 10.0             | 7.7 | 7.6 | 7.5 | 7.4 | 7.6 | 7.5 | 7.4 | 7.3 | 7.4 | 7.3 | 7.3 | 7.2 | 7.2 | 7.2 | 7.1 | 7.1 | 6.9 |     |

