

屋内照明器具特性	
品番 (品名)	XAS5020V
光源	LLD5020VCC1 ×1 1085.0 lm
管理番号	K0187898 (0) DR 1
BZ分類	BZ1

器具効率		9 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		9 2 %																						
保守率		良 中 否	0 . 6 7	0 . 6	7 4	6 8	6 4	6 1	7 3	6 7	6 3	6 1	7 2	6 7	6 3	6 1	7 1	6 6	6 3	6 0	5 9			
			0 . 6 3	0 . 8	8 0	7 4	7 1	6 8	7 9	7 4	7 0	6 8	7 8	7 3	7 0	6 7	7 6	7 2	6 9	6 7	6 6			
			0 . 5 6	1 . 0	8 4	7 9	7 5	7 2	8 3	7 8	7 5	7 2	8 1	7 7	7 4	7 2	8 0	7 6	7 4	7 1	7 0			
				1 . 2 5	8 7	8 2	7 9	7 6	8 6	8 2	7 9	7 6	8 4	8 1	7 8	7 6	8 3	8 0	7 7	7 5	7 4			
下方投影面積		c m ²	1 . 5	8 9	8 5	8 2	8 0	8 8	8 4	8 2	7 9	8 6	8 3	8 1	7 9	8 5	8 2	8 0	7 8	7 7				
等価発光面積		c m ²	2 . 0	9 2	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 9	8 6	8 4	8 2	8 7	8 5	8 3	8 2	8 0				
取付 高さ	器具間隔最大限		2 . 5	9 3	9 1	8 8	8 6	9 2	9 0	8 8	8 6	9 0	8 8	8 6	8 5	8 9	8 7	8 5	8 4	8 2				
	横方向 (A)		縦方向 (B)	3 . 0	9 4	9 2	9 0	8 8	9 3	9 1	8 9	8 8	9 1	9 0	8 8	8 7	9 0	8 8	8 7	8 6	8 4			
H m	0 . 4 5 H m	0 . 4 5 H m	4 . 0	9 6	9 4	9 2	9 1	9 5	9 3	9 1	9 0	9 3	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 6				
			5 . 0	9 7	9 5	9 4	9 2	9 6	9 4	9 3	9 2	9 3	9 2	9 1	9 0	9 2	9 1	9 0	8 9	8 7				
			7 . 0	9 7	9 6	9 5	9 4	9 6	9 5	9 4	9 4	9 4	9 4	9 3	9 2	9 2	9 2	9 1	9 0	8 8				
			1 0 . 0	9 8	9 7	9 7	9 6	9 7	9 6	9 6	9 5	9 5	9 4	9 4	9 3	9 3	9 3	9 2	9 2	8 9				

