

屋内照明器具特性

品番 (品名)	XF X4 4 0 E E N									
光源	LED5000_85_3670 x1					3670.0 lm				
管理番号	K0192935 (0) DB 1									
B Z 分類	B Z 4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		100 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
	中	0.77	0.8	6.9	5.8	5.1	4.6	6.8	5.8	5.1	4.5	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3	
	否	0.68	1.0	7.6	6.6	5.9	5.4	7.5	6.5	5.9	5.3	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.3	5.1	
	下方投影面積		1.25	8.2	7.3	6.7	6.1	8.1	7.2	6.6	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.8	
等価発光面積		1.5	8.6	7.8	7.2	6.7	8.5	7.7	7.1	6.7	8.2	7.5	7.0	6.6	7.9	7.4	6.9	6.5	6.3		
		2.0	9.1	8.5	7.9	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.1		
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.4	8.0	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.6	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.6	9.1	8.7	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.2	7.9	
1.5m	2.01m	2.13m	4.0	10.0	9.6	9.3	9.0	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.3	9.1	8.8	8.6	8.4	
2	2.66	2.69	5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.5	9.2	9.7	9.5	9.3	9.1	9.5	9.3	9.1	8.9	8.7	
2.5	3.3	3.26	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.7	9.6	9.4	9.3	9.0	
3	3.94	3.85	10.0	10.5	10.3	10.2	10.0	10.4	10.2	10.1	9.9	10.1	10.0	9.9	9.7	9.9	9.8	9.7	9.6	9.3	

