

屋内照明器具特性	
品番 (品名)	XAS5521L
光源	LLD5020LCC1 ×1 1085.0 lm
管理番号	K0187901 (0) DR 1
BZ分類	BZ1

器具効率		78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		78 %																								
保守率		良	0.67	0.6	64	59	56	54	64	59	56	54	63	58	56	53	62	58	55	53	53					
		中	0.63	0.8	69	65	62	60	69	64	62	59	67	64	61	59	66	63	61	59	58					
		否	0.56	1.0	72	68	66	63	72	68	65	63	70	67	65	63	69	66	64	63	62					
		1.25	75	71	69	67	74	71	68	67	73	70	68	66	71	69	67	66	65							
下方投影面積		c m ²		1.5	77	74	71	69	76	73	71	69	74	72	70	68	73	71	69	68	67					
		c m ²		2.0	79	76	74	72	78	76	74	72	76	74	73	71	75	73	72	71	69					
取付	器具間隔最大限			2.5	80	78	76	75	79	77	76	74	78	76	75	73	76	75	74	73	71					
高さ	横方向 (A)		縦方向 (B)	3.0	81	79	77	76	80	78	77	76	78	77	76	75	77	76	75	74	72					
H m	0.44 H m		0.44 H m	4.0	82	80	79	78	81	80	78	77	79	78	77	76	78	77	76	75	74					
				5.0	82	81	80	79	82	80	80	79	80	79	78	77	78	78	77	76	74					
				7.0	83	82	81	81	82	81	81	80	81	80	79	79	79	78	78	77	75					
				10.0	84	83	82	82	83	82	82	81	81	81	80	80	79	79	79	78	76					

