

屋内照明器具特性	
品番 (品名)	XF X4 4 0 NJ W
光源	LED4000_85_3270 x1 3270.0 lm
管理番号	K0193780(0)DB1
BZ分類	BZ4/6.0/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	12%	床	10%				10%				10%				10%				0%	
下方光束	88%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	5.9	4.8	4.1	3.6	5.7	4.7	4.0	3.5	5.4	4.5	3.9	3.5	5.1	4.3	3.8	3.4	3.1
	中	0.81	0.8	6.8	5.8	5.1	4.6	6.6	5.7	5.0	4.5	6.2	5.4	4.9	4.4	5.9	5.2	4.7	4.3	4.0
	否	0.77	1.0	7.5	6.5	5.8	5.3	7.2	6.4	5.7	5.2	6.8	6.1	5.5	5.1	6.4	5.8	5.3	5.0	4.6
			1.25	8.0	7.1	6.5	6.0	7.8	7.0	6.4	5.9	7.3	6.7	6.1	5.7	6.9	6.3	5.9	5.6	5.2
下方投影面積		cm ²	1.5	8.4	7.6	7.0	6.5	8.1	7.4	6.8	6.4	7.7	7.1	6.6	6.2	7.2	6.7	6.3	6.0	5.6
等価発光面積		cm ²	2.0	8.9	8.2	7.7	7.2	8.6	8.0	7.5	7.1	8.1	7.6	7.2	6.8	7.7	7.3	6.9	6.6	6.2
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.7	8.9	8.4	7.9	7.6	8.4	8.0	7.6	7.3	8.0	7.6	7.3	7.0	6.5
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.1	9.1	8.7	8.3	7.9	8.6	8.2	7.9	7.6	8.2	7.9	7.6	7.3	6.8
1.5m	1.9m	2.06m	4.0	9.7	9.2	8.9	8.6	9.4	9.0	8.7	8.4	8.9	8.6	8.3	8.1	8.4	8.2	8.0	7.7	7.2
2	2.52	2.6	5.0	9.8	9.5	9.2	8.9	9.6	9.2	9.0	8.7	9.1	8.8	8.6	8.4	8.6	8.4	8.2	8.0	7.5
2.5	3.14	3.17	7.0	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.5	8.3	7.8
3	3.75	3.75	10.0	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.4	9.3	9.1	9.0	8.9	8.8	8.7	8.6	8.0

