

屋内照明器具特性	
品番 (品名)	XF X4 4 0 P J N
光源	LED5000_85_3380 x1 3380.0 lm
管理番号	K0193751(0)DB1
BZ分類	BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	63	52	45	40	61	51	45	40	59	50	44	40	57	49	44	40	38
	中	0.77	0.8	73	63	56	51	72	62	56	51	69	61	55	51	67	60	55	51	49
	否	0.68	1.0	79	70	64	59	78	70	63	59	75	68	63	58	73	67	62	58	56
			1.25	85	77	71	66	83	76	70	66	81	74	69	65	78	73	69	65	63
下方投影面積	c m ²		1.5	89	81	76	71	87	80	75	71	84	79	74	70	82	77	73	70	68
	等価発光面積		c m ²	2.0	93	88	83	79	92	87	82	78	89	85	81	78	87	83	80	77
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	87	83	92	88	85	82	90	87	84	81	79
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	90	87	94	91	88	86	92	89	87	84	82
1.5m	1.87m	2.08m	4.0	101	98	95	92	100	96	94	91	97	94	92	90	95	92	90	89	86
2	2.48	2.63	5.0	102	100	97	95	101	99	96	94	99	96	94	93	96	94	93	91	89
2.5	3.09	3.2	7.0	104	102	100	98	103	101	99	98	100	99	97	96	98	97	96	94	92
3	3.69	3.79	10.0	105	104	103	101	104	103	102	100	102	101	100	99	99	98	98	97	94

