

屋内照明器具特性	
品番 (品名)	XF X4 4 0 UL W
光源	LED4000_85_3490 x1 3490.0 lm
管理番号	K0193748 (0) DB 1
BZ分類	BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.9	4.7	4.0	3.4	5.8	4.7	3.9	3.4	5.5	4.6	3.9	3.4	5.3	4.5	3.8	3.4	3.2
	中	0.77	0.8	6.9	5.8	5.1	4.5	6.8	5.7	5.0	4.5	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3
	否	0.68	1.0	7.6	6.6	5.8	5.3	7.4	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0
			1.25	8.2	7.2	6.6	6.0	8.0	7.2	6.5	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.7
下方投影面積		cm ²	1.5	8.6	7.7	7.1	6.6	8.4	7.6	7.0	6.6	8.1	7.5	6.9	6.5	7.8	7.3	6.8	6.4	6.2
等価発光面積		cm ²	2.0	9.1	8.4	7.9	7.4	8.9	8.3	7.8	7.4	8.6	8.1	7.7	7.3	8.4	7.9	7.5	7.2	7.0
取付高さ	器具間隔最大限		2.5	9.4	8.9	8.4	8.0	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.5
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.7	8.4	9.5	9.1	8.7	8.3	9.2	8.8	8.5	8.2	9.0	8.6	8.3	8.1	7.8
1.5m	1.93m	2.11m	4.0	10.0	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	9.0	8.7	9.3	9.0	8.8	8.6	8.3
2	2.55	2.65	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.2	9.7	9.5	9.2	9.0	9.5	9.3	9.1	8.9	8.6
2.5	3.18	3.22	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.7	9.5	9.4	9.3	9.0
3	3.79	3.8	10.0	10.5	10.3	10.1	10.0	10.4	10.2	10.0	9.9	10.1	10.0	9.8	9.7	9.9	9.8	9.6	9.5	9.3

