

屋内照明器具特性

品番 (品名)	XF X4 4 0 VEL									
光源	LED3000_85_3560 x1					3560.0 lm				
管理番号	K0192147(0)D 1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%																			
下方光束	100%																			
		反射率																		
			床	10%				10%				10%				10%				0%
			室指数	照明率 (X0.01)																ZCM
保守率	良	0.81	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.3	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8
	中	0.77	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.2	5.2	4.6	4.0	5.9	5.1	4.5	4.0	3.8
	否	0.68	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.4	4.8	6.8	5.9	5.3	4.8	6.6	5.8	5.2	4.7	4.5
			0.68	1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.5	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.5
下方投影面積																				
等価発光面積																				
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
1.5m	1.96m	2.11m	4.0	9.5	8.9	8.4	8.0	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.5
2	2.59	2.65	5.0	10.0	9.7	9.3	9.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.3	9.1	8.9	8.7	8.4
2.5	3.22	3.22	7.0	10.3	10.0	9.7	9.5	10.1	9.9	9.6	9.4	9.8	9.6	9.4	9.2	9.6	9.4	9.2	9.1	8.8
3	3.85	3.8	10.0	10.4	10.2	10.0	9.9	10.3	10.1	9.9	9.8	10.0	9.9	9.7	9.6	9.8	9.7	9.5	9.4	9.1

