

屋内照明器具特性	
品番 (品名)	XAS3002
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178920 (0) DR1
BZ分類	BZ4

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	53	42	35	31	51	42	35	31	49	41	35	30	47	40	34	30	29
			0.63	0.8	62	52	45	41	60	51	45	40	58	50	44	40	56	49	44	40	38
			0.56	1.0	68	59	52	48	66	58	52	47	64	57	51	47	62	55	51	47	45
				1.25	73	65	59	54	72	64	59	54	69	63	58	54	67	61	57	53	51
下方投影面積 等価発光面積		cm ² cm ²		1.5	77	69	64	59	75	69	63	59	73	67	62	59	70	65	61	58	56
				2.0	81	76	71	67	80	75	70	66	78	73	69	66	75	71	68	65	63
				2.5	84	79	75	72	83	78	75	71	81	77	73	70	78	75	72	69	67
				3.0	86	82	78	75	85	81	78	75	83	79	76	74	80	77	75	73	70
H m	1.29 H m	1.29 H m		4.0	89	86	83	80	88	85	82	79	85	83	80	78	83	81	79	77	75
				5.0	91	88	85	83	89	87	84	82	87	85	83	81	85	83	81	80	77
				7.0	92	90	88	86	91	89	87	86	89	87	86	84	87	85	84	83	80
				10.0	94	92	91	89	92	91	90	88	90	89	88	87	88	87	86	85	83

