

屋内照明器具特性	
品番 (品名)	XAD1100K
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0178932 (0) DR 1
BZ分類	BZ4/1.4/BZ3

器具効率		87 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	52	42	36	31	51	42	36	31	49	41	35	31	48	40	35	31	30				
			0.63	0.8	62	52	46	41	60	52	46	41	58	51	45	41	56	50	45	41	39				
			0.56	1.0	67	59	53	48	66	58	53	48	64	57	52	48	62	56	51	48	46				
				1.25	73	65	60	55	71	64	59	55	69	63	58	55	67	62	58	54	52				
下方投影面積 等価発光面積		cm ² cm ²		1.5	76	69	64	60	75	69	64	60	72	67	63	59	70	66	62	59	57				
				2.0	81	75	71	67	79	74	70	67	77	73	69	66	75	71	68	65	63				
				2.5	84	79	75	72	82	78	74	71	80	76	73	70	78	75	72	70	68				
				3.0	85	81	78	75	84	80	77	75	82	79	76	74	80	77	75	73	70				
H m	1.25 H m	1.25 H m		4.0	88	85	82	79	87	84	81	79	84	82	80	78	82	80	78	77	74				
				5.0	89	87	84	82	88	86	83	82	86	84	82	80	84	82	80	79	77				
				7.0	91	89	87	85	90	88	86	85	87	86	85	83	85	84	83	82	80				
				10.0	92	91	89	88	91	90	88	87	89	88	87	86	87	86	85	84	82				

