

屋内照明器具特性

品番 (品名)	XF X4 4 3 E E N				
光源	LED5000_85_2820 x1 2820.0 1 m				
管理番号	K0192937 (0) DB 1				
B Z 分類	BZ4 / 0.7 / BZ3 / 2.8 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81	0.6	61	50	43	38	60	50	43	38	58	49	42	38	56	48	42	38	36
		0.77	0.8	73	63	56	52	72	63	56	51	69	61	56	51	67	60	55	51	49
		0.68	1.0	80	72	65	61	79	71	65	60	77	69	64	60	74	68	63	60	58
			1.25	86	79	73	69	85	78	73	68	82	76	72	68	80	75	71	67	65
下方投影面積	c m ²	1.5	90	83	78	74	89	82	78	74	86	81	76	73	84	79	75	72	70	
		2.0	95	89	85	81	93	88	84	81	91	87	83	80	89	85	82	79	77	
取付高さ	器具間隔最大限		2.5	98	93	89	86	96	92	89	86	94	90	87	85	91	88	86	84	81
	横方向 (A)	縦方向 (B)	3.0	99	96	92	89	98	95	92	89	96	93	90	88	93	91	89	87	84
1.5m	2.46 m	2.06 m	4.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	92	90	88
2	3.24	2.59	5.0	103	101	98	96	102	100	98	96	99	98	96	94	97	96	94	93	90
2.5	4.02	3.13	7.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	97	96	93
3	4.79	3.69	10.0	106	105	103	102	105	103	102	101	102	101	100	99	100	99	98	98	95

