

|          |                              |
|----------|------------------------------|
| 屋内照明器具特性 |                              |
| 品番(品名)   | XF X4 4 6 F E V              |
| 光源       | LED3500_85_2460 x1 2460.0 lm |
| 管理番号     | K0192934(0)DB1               |
| BZ分類     | BZ4                          |

|        |                  |        |               |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    |     |    |
|--------|------------------|--------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%             | 天井     | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |    |    | 0%  |    |
|        |                  | 壁      | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%               | 床      | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%             | 室指数    | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    | ZCM |    |
| 保守率    | 良<br>中<br>否      | 0.77   | 0.6           | 60  | 49  | 42  | 37  | 59  | 48  | 41  | 37  | 57  | 47  | 41 | 36  | 55 | 46 | 41 | 36  | 34 |
|        |                  | 0.72   | 0.8           | 70  | 60  | 52  | 47  | 69  | 59  | 52  | 47  | 66  | 58  | 51 | 47  | 64 | 56 | 51 | 47  | 45 |
|        |                  | 0.68   | 1.0           | 77  | 67  | 60  | 55  | 75  | 66  | 60  | 55  | 73  | 65  | 59 | 54  | 70 | 63 | 58 | 54  | 52 |
|        |                  |        | 1.25          | 82  | 74  | 67  | 62  | 81  | 73  | 67  | 62  | 78  | 71  | 66 | 61  | 76 | 70 | 65 | 61  | 59 |
| 下方投影面積 | c m <sup>2</sup> | 1.5    | 86            | 78  | 72  | 67  | 85  | 77  | 72  | 67  | 82  | 76  | 71  | 66 | 79  | 74 | 70 | 66 | 64  |    |
|        |                  | 2.0    | 92            | 85  | 80  | 75  | 90  | 84  | 79  | 75  | 87  | 82  | 78  | 74 | 85  | 80 | 76 | 73 | 71  |    |
| 取付高さ   | 器具間隔最大限          |        | 2.5           | 95  | 89  | 84  | 80  | 93  | 88  | 84  | 80  | 90  | 86  | 82 | 79  | 88 | 84 | 81 | 78  | 76 |
|        | 横方向(A)           | 縦方向(B) | 3.0           | 97  | 92  | 88  | 84  | 96  | 91  | 87  | 84  | 93  | 89  | 86 | 83  | 90 | 87 | 84 | 82  | 79 |
| 1.5m   | 1.71m            | 2.05m  | 4.0           | 100 | 96  | 93  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 90 | 88  | 93 | 91 | 88 | 86  | 84 |
| 2      | 2.26             | 2.57   | 5.0           | 101 | 98  | 96  | 93  | 100 | 97  | 95  | 92  | 97  | 95  | 93 | 91  | 95 | 93 | 91 | 89  | 87 |
| 2.5    | 2.81             | 3.12   | 7.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96 | 94  | 97 | 96 | 94 | 93  | 90 |
| 3      | 3.36             | 3.67   | 10.0          | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99 | 97  | 99 | 98 | 97 | 96  | 93 |

