

# 屋内照明器具特性

品番 (品名)	XF X4 4 9 DED									
光源	LED6500_85_3860 x1					3860.0 lm				
管理番号	K0192925(0)DB1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
		床	10 %				10 %				10 %				10 %				0 %		
上方光束	4 %																				
下方光束	96 %																				
室指数	照明率 ( X0.01 )																		ZCM		
保守率	良 中 否	0.83	0.6	5.6	4.3	3.5	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.4	2.9	2.7	
		0.81	0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.9	3.6	
		0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.6	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.3	
			1.25	7.8	6.8	6.0	5.4	7.6	6.6	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.2	4.9	
下方投影面積		cm <sup>2</sup>																			
等価発光面積		cm <sup>2</sup>																			
取付高さ	器具間隔最大限		2.5																		
	横方向 (A)	縦方向 (B)		3.0																	
1.5m	1.97m	2.13m	4.0																		
2	2.6	2.67	5.0																		
2.5	3.23	3.23	7.0																		
3	3.86	3.81	10.0																		

