

屋内照明器具特性	
品番 (品名)	XAS3522N
光源	LED5000_70_690 ×1 690.0 l m
管理番号	K0170908 (1) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		1 0 0 %																						
保守率		良	0 . 6 7	0 . 6	8 4	7 8	7 4	7 1	8 3	7 7	7 4	7 1	8 2	7 7	7 3	7 1	8 1	7 6	7 3	7 1	7 0			
		中	0 . 6 3	0 . 8	9 0	8 4	8 1	7 8	8 9	8 4	8 0	7 8	8 7	8 3	8 0	7 8	8 6	8 2	7 9	7 7	7 6			
		否	0 . 5 6	1 . 0	9 3	8 8	8 5	8 2	9 2	8 8	8 5	8 2	9 1	8 7	8 4	8 2	8 9	8 6	8 3	8 1	8 0			
		1 . 2 5	9 6	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 4	9 0	8 8	8 6	9 2	8 9	8 7	8 5	8 4					
下方投影面積 等価発光面積		c m ²	1 . 5	9 8	9 5	9 2	8 9	9 7	9 4	9 1	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 8	8 6				
			2 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 9				
			2 . 5	1 0 2	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 1				
取付 高さ	器具間隔最大限		3 . 0	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 3				
	横方向 (A)	縦方向 (B)	4 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 7	9 4				
H m	0 . 4 1 H m	0 . 4 1 H m	5 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5				
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7				
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 7				

