

屋内照明器具特性	
品番 (品名)	XAS5020V
光源	LLD5020VCC1 ×1 1085.0 lm
管理番号	K0187898 (0) DR1
BZ分類	BZ1

器具効率			92 %	天井	80 %				70 %				50 %				30 %				0 %					
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
						床	10 %				10 %				10 %				10 %				0 %			
上方光束			0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束			92 %																							
保守率			良 中 否	0.67	0.6	74	68	64	61	73	67	63	61	72	67	63	61	71	66	63	60	59				
				0.63	0.8	80	74	71	68	79	74	70	68	78	73	70	67	76	72	69	67	66				
				0.56	1.0	84	79	75	72	83	78	75	72	81	77	74	72	80	76	74	71	70				
				1.25	87	82	79	76	86	82	79	76	84	81	78	76	83	80	77	75	74					
下方投影面積			c m ²	1.5	89	85	82	80	88	84	82	79	86	83	81	79	85	82	80	78	77					
				2.0	92	89	86	84	91	88	85	83	89	86	84	82	87	85	83	82	80					
取付 高さ	器具間隔最大限			2.5	93	91	88	86	92	90	88	86	90	88	86	85	89	87	85	84	82					
	横方向 (A)		縦方向 (B)	3.0	94	92	90	88	93	91	89	88	91	90	88	87	90	88	87	86	84					
H m	0.45 H m		0.45 H m	4.0	96	94	92	91	95	93	91	90	93	91	90	89	91	90	89	88	86					
				5.0	97	95	94	92	96	94	93	92	93	92	91	90	92	91	90	89	87					
				7.0	97	96	95	94	96	95	94	94	94	94	93	92	92	92	91	90	88					
				10.0	98	97	97	96	97	96	96	95	95	94	94	93	93	93	92	92	89					

