

屋内照明器具特性	
品番 (品名)	XF X450CEW
光源	LED4000_85_4850 x1 4850.0 lm
管理番号	K0192157(0)D 1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 (X0.01) ZCM																	
保守率	良 0.83 中 0.81 否 0.77	0.6	51	39	31	25	49	37	30	24	45	35	28	23	41	33	27	22	19	
		0.8	60	48	40	34	58	47	39	33	53	44	37	32	49	41	35	30	26	
		1.0	67	55	47	40	64	53	45	39	59	50	43	38	54	46	40	36	32	
		1.25	72	62	53	47	69	60	52	46	64	56	49	44	59	52	46	42	37	
下方投影面積	c m ²	1.5	77	66	59	52	73	64	57	51	68	60	54	49	62	56	51	46	41	
		2.0	82	73	66	60	79	71	64	59	73	66	61	56	67	62	57	53	48	
取付高さ	器具間隔最大限		2.5	86	78	72	66	83	76	70	64	76	71	66	61	71	66	62	58	52
	横方向 (A)	縦方向 (B)	3.0	88	82	76	71	85	79	73	69	79	74	69	65	73	69	65	62	55
1.5m	1.97m	2.11m	4.0	92	86	81	77	89	83	79	75	82	78	74	71	76	73	70	67	60
2	2.59	2.64	5.0	94	89	85	81	91	86	82	79	85	81	78	74	79	76	73	70	64
2.5	3.23	3.2	7.0	97	93	89	86	93	90	87	84	87	84	82	79	81	79	77	75	68
3	3.85	3.78	10.0	99	96	93	91	96	93	90	88	89	87	85	83	84	82	80	79	71

