

| | |
|----------|------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XF X4 5 0 KHW |
| 光源 | LED4000_85_4850 x1 4850.0 lm |
| 管理番号 | K0192151(0)D 1 |
| BZ分類 | BZ5/2.8/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|----------------------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 1% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 99% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.81 中 0.77 否 0.68 | 0.6 | 57 | 45 | 37 | 32 | 56 | 44 | 37 | 32 | 53 | 43 | 36 | 31 | 51 | 42 | 36 | 31 | 29 | |
| | | 0.8 | 67 | 56 | 48 | 42 | 66 | 55 | 47 | 42 | 63 | 53 | 47 | 42 | 60 | 52 | 46 | 41 | 39 | |
| | | 1.0 | 74 | 63 | 55 | 50 | 72 | 62 | 55 | 50 | 69 | 61 | 54 | 49 | 66 | 59 | 53 | 49 | 46 | |
| | | 1.25 | 80 | 70 | 63 | 57 | 78 | 69 | 62 | 57 | 75 | 67 | 61 | 57 | 72 | 66 | 60 | 56 | 54 | |
| 下方投影面積 | cm ² | 1.5 | 84 | 75 | 68 | 63 | 82 | 74 | 68 | 63 | 79 | 72 | 67 | 62 | 76 | 70 | 65 | 61 | 59 | |
| | | 2.0 | 90 | 82 | 76 | 72 | 88 | 81 | 76 | 71 | 85 | 79 | 74 | 70 | 82 | 77 | 73 | 69 | 67 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 93 | 87 | 82 | 77 | 91 | 86 | 81 | 77 | 88 | 84 | 79 | 76 | 86 | 81 | 78 | 75 | 72 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 96 | 90 | 86 | 82 | 94 | 89 | 85 | 81 | 91 | 87 | 83 | 80 | 88 | 85 | 82 | 79 | 76 |
| 1.5m | 1.94m | 2.11m | 4.0 | 99 | 95 | 91 | 87 | 97 | 93 | 90 | 87 | 94 | 91 | 88 | 85 | 92 | 89 | 86 | 84 | 81 |
| 2 | 2.56 | 2.66 | 5.0 | 101 | 97 | 94 | 91 | 99 | 96 | 93 | 90 | 96 | 94 | 91 | 89 | 94 | 91 | 89 | 87 | 84 |
| 2.5 | 3.18 | 3.22 | 7.0 | 103 | 100 | 98 | 96 | 101 | 99 | 97 | 95 | 99 | 97 | 95 | 93 | 96 | 94 | 93 | 91 | 88 |
| 3 | 3.8 | 3.81 | 10.0 | 104 | 103 | 101 | 99 | 103 | 101 | 100 | 98 | 100 | 99 | 98 | 96 | 98 | 97 | 95 | 94 | 91 |

