

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | XF X4 5 0 PHN      |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_85_4940 x1 |  |  |  |  | 4940.0 lm |  |  |  |  |
| 管理番号    | K0192926(0)DB1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5/1.4/BZ4        |  |  |  |  |           |  |  |  |  |

|        |         |                 |              |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%          |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%          |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.81            | 0.6          | 57  | 45  | 37  | 32  | 56  | 44  | 37  | 32  | 54  | 43 | 37 | 32  | 51 | 42 | 36 | 32  | 30 |
|        | 中       | 0.77            | 0.8          | 67  | 56  | 48  | 42  | 66  | 55  | 48  | 42  | 63  | 54 | 47 | 42  | 61 | 53 | 47 | 42  | 40 |
|        | 否       | 0.68            | 1.0          | 74  | 63  | 56  | 50  | 72  | 63  | 55  | 50  | 70  | 61 | 55 | 50  | 67 | 60 | 54 | 49  | 47 |
|        |         |                 | 1.25         | 80  | 71  | 63  | 58  | 78  | 70  | 63  | 58  | 75  | 68 | 62 | 57  | 73 | 66 | 61 | 57  | 54 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5          | 84  | 76  | 69  | 64  | 83  | 75  | 68  | 63  | 80  | 73 | 67 | 63  | 77 | 71 | 66 | 62  | 60 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0          | 90  | 83  | 77  | 72  | 88  | 82  | 76  | 72  | 85  | 80 | 75 | 71  | 83 | 78 | 74 | 70  | 68 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5          | 93  | 87  | 82  | 78  | 92  | 86  | 81  | 77  | 89  | 84 | 80 | 76  | 86 | 82 | 79 | 75  | 73 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0          | 96  | 91  | 86  | 82  | 94  | 90  | 85  | 82  | 91  | 87 | 84 | 80  | 89 | 85 | 82 | 79  | 77 |
| 1.5m   | 1.94m   | 2.13m           | 4.0          | 99  | 95  | 91  | 88  | 98  | 94  | 90  | 87  | 95  | 92 | 89 | 86  | 92 | 89 | 87 | 85  | 82 |
| 2      | 2.57    | 2.69            | 5.0          | 101 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94 | 92 | 89  | 94 | 92 | 90 | 88  | 85 |
| 2.5    | 3.2     | 3.26            | 7.0          | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 94  | 97 | 95 | 93 | 92  | 89 |
| 3      | 3.82    | 3.85            | 10.0         | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99 | 98 | 97  | 98 | 97 | 96 | 95  | 92 |

