

屋内照明器具特性	
品番 (品名)	XAD3 1 0 1 L K
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0175547 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	39	32	27	24	38	31	27	24	37	31	27	24	35	30	26	24	23
			0.63	0.8	46	39	35	31	45	39	34	31	43	38	34	31	42	37	34	31	30
			0.56	1.0	50	44	40	37	49	44	40	36	47	43	39	36	46	42	39	36	35
				1.25	54	48	45	41	53	48	44	41	51	47	44	41	49	46	43	41	39
下方投影面積		c m ²		1.5	56	51	48	45	55	51	47	45	53	50	47	44	52	49	46	44	43
			等価発光面積	c m ²	2.0	59	56	52	50	58	55	52	50	57	54	51	49	55	53	50	49
取付 高さ	器具間隔最大限			2.5	61	58	55	53	60	57	55	53	59	56	54	52	57	55	53	51	50
	横方向 (A) 縦方向 (B)			3.0	63	60	57	55	62	59	57	55	60	58	56	54	58	57	55	54	52
H m	1.25 H m	1.25 H m		4.0	64	62	60	58	63	61	60	58	62	60	58	57	60	59	57	56	55
				5.0	65	63	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56
				7.0	66	65	64	63	65	64	63	62	64	63	62	61	62	62	61	60	58
				10.0	67	66	65	64	66	65	65	64	65	64	63	63	63	63	62	62	60

