

屋内照明器具特性

品番 (品名)	S L W4 5 9 4 1									
光源	LED2700_70_110 x1 110.0 l m									
管理番号	K0151814 (0) DB 1									
B Z 分類	BZ10 / 1.4 / BZ9									

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		8 1 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 9 %																				
保守率		良	0 . 6 9	0 . 6	4 3	3 1	2 4	1 9	3 7	2 8	2 1	1 7	2 7	2 0	1 6	1 2	1 8	1 3	1 0	8	1	
		中	0 . 6 7	0 . 8	5 1	4 0	3 2	2 7	4 4	3 5	2 8	2 4	3 2	2 6	2 1	1 7	2 2	1 7	1 4	1 1	2	
		否	0 . 6 3	1 . 0	5 7	4 6	3 9	3 3	4 9	4 1	3 4	2 9	3 6	3 0	2 5	2 2	2 4	2 0	1 7	1 4	3	
				1 . 2 5	6 2	5 2	4 5	3 9	5 4	4 6	4 0	3 5	4 0	3 4	3 0	2 6	2 7	2 3	2 0	1 8	5	
下方投影面積		c m ²		1 . 5	6 6	5 7	5 0	4 4	5 8	5 0	4 4	3 9	4 3	3 7	3 3	3 0	2 9	2 5	2 3	2 0	6	
等価発光面積		c m ²		2 . 0	7 1	6 3	5 7	5 2	6 3	5 6	5 1	4 6	4 6	4 2	3 8	3 5	3 2	2 9	2 6	2 4	7	
取付高さ	器具間隔最大限			2 . 5	7 4	6 8	6 2	5 7	6 6	6 0	5 5	5 1	4 9	4 5	4 2	3 9	3 3	3 1	2 9	2 7	9	
	横方向 (A)		縦方向 (B)	3 . 0	7 7	7 1	6 6	6 1	6 8	6 3	5 9	5 5	5 1	4 7	4 4	4 2	3 5	3 3	3 1	2 9	1 0	
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	8 0	7 5	7 1	6 7	7 1	6 7	6 3	6 0	5 3	5 0	4 8	4 5	3 7	3 5	3 3	3 1	1 1		
			5 . 0	8 2	7 8	7 4	7 1	7 2	6 9	6 6	6 3	5 5	5 2	5 0	4 8	3 8	3 6	3 5	3 3	1 2		
			7 . 0	8 4	8 1	7 8	7 5	7 5	7 2	7 0	6 7	5 7	5 5	5 3	5 1	3 9	3 8	3 7	3 6	1 3		
			1 0 . 0	8 6	8 4	8 1	7 9	7 6	7 4	7 2	7 1	5 8	5 7	5 5	5 4	4 1	4 0	3 9	3 8	1 4		

