

屋内照明器具特性	
品番(品名)	XF X430CEW
光源	LED4000_85_2980 x1 2980.0lm
管理番号	K0192157(0)D 1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	51	39	31	25	49	37	30	24	45	35	28	23	41	33	27	22	19	
		0.8	60	48	40	34	58	47	39	33	53	44	37	32	49	41	35	30	26	
		1.0	67	55	47	40	64	53	45	39	59	50	43	38	54	46	40	36	32	
		1.25	72	62	53	47	69	60	52	46	64	56	49	44	59	52	46	42	37	
下方投影面積	c m ²	1.5	77	66	59	52	73	64	57	51	68	60	54	49	62	56	51	46	41	
		2.0	82	73	66	60	79	71	64	59	73	66	61	56	67	62	57	53	48	
取付高さ	器具間隔最大限		2.5	86	78	72	66	83	76	70	64	76	71	66	61	71	66	62	58	52
	横方向(A)	縦方向(B)	3.0	88	82	76	71	85	79	73	69	79	74	69	65	73	69	65	62	55
1.5m	1.97m	2.11m	4.0	92	86	81	77	89	83	79	75	82	78	74	71	76	73	70	67	60
2	2.59	2.64	5.0	94	89	85	81	91	86	82	79	85	81	78	74	79	76	73	70	64
2.5	3.23	3.2	7.0	97	93	89	86	93	90	87	84	87	84	82	79	81	79	77	75	68
3	3.85	3.78	10.0	99	96	93	91	96	93	90	88	89	87	85	83	84	82	80	79	71

