

屋内照明器具特性	
品番 (品名)	S N C X 5 1 1 2 0
光源	LED6200_70_5499 ×1 5499.0 lm
管理番号	K0182582 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 3	3 5	2 9	5 3	4 2	3 4	2 9	5 0	4 0	3 3	2 9	4 8	3 9	3 3	2 8	2 6	
			0 . 6	0 . 8	6 5	5 3	4 5	3 9	6 3	5 2	4 5	3 9	5 9	5 0	4 3	3 8	5 6	4 8	4 2	3 8	3 5	
			0 . 5 6	1 . 0	7 1	6 1	5 3	4 7	6 9	5 9	5 2	4 6	6 6	5 7	5 0	4 5	6 2	5 5	4 9	4 5	4 2	
				1 . 2 5	7 7	6 8	6 0	5 4	7 5	6 6	5 9	5 4	7 1	6 4	5 7	5 3	6 8	6 1	5 6	5 1	4 8	
下方投影面積		c m ²	1 . 5	8 2	7 3	6 5	6 0	7 9	7 1	6 4	5 9	7 5	6 8	6 3	5 8	7 2	6 6	6 1	5 7	5 3		
			等価発光面積	2 . 0	8 7	8 0	7 3	6 8	8 5	7 8	7 2	6 7	8 1	7 5	7 0	6 6	7 7	7 2	6 8	6 4	6 1	
取付 高さ	器具間隔最大限			2 . 5	9 1	8 4	7 9	7 4	8 9	8 3	7 7	7 3	8 4	7 9	7 5	7 1	8 1	7 6	7 3	6 9	6 6	
	横方向 (A)		縦方向 (B)	3 . 0	9 3	8 8	8 3	7 8	9 1	8 6	8 1	7 7	8 7	8 3	7 9	7 5	8 3	7 9	7 6	7 3	6 9	
H m	1 . 3 0 H m		1 . 3 0 H m	4 . 0	9 7	9 2	8 8	8 4	9 4	9 0	8 6	8 3	9 0	8 7	8 4	8 1	8 6	8 4	8 1	7 8	7 4	
				5 . 0	9 8	9 5	9 1	8 8	9 6	9 3	9 0	8 7	9 2	8 9	8 7	8 4	8 9	8 6	8 4	8 2	7 8	
				7 . 0	1 0 1	9 8	9 5	9 3	9 9	9 6	9 4	9 1	9 5	9 3	9 0	8 9	9 1	8 9	8 7	8 6	8 1	
				1 0 . 0	1 0 3	1 0 0	9 8	9 7	1 0 1	9 9	9 7	9 5	9 7	9 5	9 4	9 2	9 3	9 2	9 0	8 9	8 5	

