

屋内照明器具特性	
品番 (品名)	S N C X 5 8 3 0 0
光源	LED6200_70_5499 ×1 5499.0 lm
管理番号	K0181799 (0) DR 1
B Z 分類	BZ6 / 1.1 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		26 % 74 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	51	39	31	26	48	37	30	25	44	34	28	23	39	31	26	22	18
			0.6	0.8	60	48	40	35	57	46	39	34	51	43	36	31	46	39	34	29	25
			0.56	1.0	67	55	47	41	63	53	46	40	57	49	42	38	51	44	39	35	30
			1.25	72	62	54	48	69	59	52	47	62	54	48	44	56	50	45	41	35	
下方投影面積 等価発光面積		cm ² cm ²	1.5	76	67	60	54	73	64	57	52	66	59	53	49	59	54	49	45	39	
			2.0	82	74	67	62	78	71	65	60	71	65	60	56	64	59	55	52	45	
取付 高さ	器具間隔最大限		2.5	86	79	73	68	82	75	70	65	74	69	65	61	67	63	60	56	49	
	横方向 (A) 縦方向 (B)		3.0	88	82	77	72	84	79	74	70	77	72	68	65	70	66	63	60	52	
1.5m	2.02 m	1.95 m	4.0	91	86	82	78	87	83	79	75	80	76	73	70	73	70	67	65	56	
2	2.66	2.56	5.0	94	89	86	82	90	86	82	79	82	79	76	73	75	72	70	68	59	
2.5	3.32	3.19	7.0	96	93	90	87	92	89	86	84	84	82	80	78	77	75	73	72	63	
3	3.94	3.8	10.0	98	95	93	91	94	92	90	88	86	85	83	81	79	78	76	75	66	

