

屋内照明器具特性	
品番 (品名)	S P L 5 4 2 9
光源	LLD4000LCE1 ×4 845.0 l m
管理番号	K0183106 (0) DB 1
B Z 分類	BZ5

器具効率		76 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		76 %																						
保守率		良 中 否	0.67	0.6	43	34	28	24	42	34	28	24	41	33	28	24	39	32	27	24	22			
			0.63	0.8	51	42	36	32	50	42	36	32	48	41	36	32	46	40	35	32	30			
			0.56	1.0	56	48	42	38	55	47	42	38	53	46	41	37	51	45	41	37	35			
				1.25	61	53	48	44	59	53	47	43	57	51	47	43	55	50	46	43	41			
下方投影面積		c m ²		1.5	64	57	52	48	63	56	52	48	60	55	51	47	58	54	50	47	45			
等価発光面積			c m ²	2.0	68	63	58	54	67	62	58	54	65	60	56	53	62	59	56	53	51			
取付 高さ	器具間隔最大限			2.5	71	66	62	59	70	65	61	58	67	64	60	58	65	62	59	57	55			
	横方向 (A)		縦方向 (B)	3.0	73	69	65	62	72	68	64	61	69	66	63	61	67	64	62	60	58			
H m	1.27 H m	1.27 H m		4.0	75	72	69	66	74	71	68	66	72	69	67	65	70	68	66	64	62			
				5.0	77	74	71	69	75	73	71	69	73	71	69	67	71	70	68	66	64			
				7.0	78	76	74	73	77	75	74	72	75	74	72	71	73	72	71	70	67			
				10.0	79	78	77	75	78	77	76	75	77	75	74	73	75	74	73	72	70			

