

屋内照明器具特性	
品番 (品名)	S P L 5 4 2 9
光源	LLD2000LCE1 ×4 531.0 lm
管理番号	K0183107 (0) DB 1
B Z 分類	BZ5

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z CM	
下方光束		77 %																					
保守率		良 中 否	0.67	0.6	44	35	29	24	43	34	28	24	41	33	28	24	39	33	28	24	23		
			0.63	0.8	52	43	37	33	51	42	37	32	49	41	36	32	47	40	36	32	30		
			0.56	1.0	57	49	43	38	56	48	43	38	53	47	42	38	51	46	41	38	36		
				1.25	62	54	49	44	60	53	48	44	58	52	47	44	56	51	47	43	42		
下方投影面積		cm ²	1.5	65	58	53	49	64	57	52	48	61	56	51	48	59	54	51	47	46			
等価発光面積		cm ²	2.0	69	63	59	55	68	63	58	55	66	61	57	54	63	60	56	54	52			
取付 高さ	器具間隔最大限			2.5	72	67	63	60	71	66	62	59	68	65	61	58	66	63	60	58	56		
	横方向 (A)		縦方向 (B)	3.0	74	70	66	63	73	69	65	62	70	67	64	62	68	65	63	61	59		
H m	1.26 H m	1.26 H m	4.0	76	73	70	67	75	72	69	67	73	70	68	66	71	69	67	65	63			
			5.0	78	75	72	70	76	74	72	70	74	72	70	68	72	71	69	67	65			
			7.0	79	77	75	74	78	76	75	73	76	75	73	72	74	73	72	71	68			
			10.0	81	79	78	76	80	78	77	76	78	76	75	74	76	75	74	73	71			

