

屋内照明器具特性	
品番 (品名)	P A V 1 2 5 4 5 D L W P W 4 0 + N T S 9 0 3 5 5
光源	L E D 4 0 0 0 _ 7 0 _ 1 5 9 5 x 1 1 5 9 5 . 0 l m
管理番号	K 0 1 7 9 7 1 4 (1) D R 1
B Z 分類	B Z 1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 1 %																				
保守率		良 中 否	0 . 6	9 4	9 0	8 8	8 6	9 3	9 0	8 7	8 6	9 3	8 9	8 7	8 6	9 2	8 9	8 7	8 5	8 5		
			0 . 6	9 8	9 4	9 2	9 0	9 7	9 4	9 2	9 0	9 6	9 3	9 1	9 0	9 5	9 3	9 1	8 9	8 9		
			1 . 0	1 0 0	9 7	9 5	9 3	9 9	9 6	9 4	9 3	9 8	9 6	9 4	9 2	9 7	9 5	9 3	9 2	9 1		
			0 . 5 6	1 . 2 5	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 7	9 5	1 0 0	9 7	9 6	9 4	9 8	9 7	9 5	9 4	9 3	
下方投影面積		c m ²	1 . 5	1 0 3	1 0 0	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 1	9 9	9 7	9 6	9 9	9 8	9 6	9 5	9 4		
			等価発光面積		c m ²	2 . 0	1 0 5	1 0 2	1 0 1	9 9	1 0 4	1 0 2	1 0 0	9 9	1 0 2	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7
取付 高さ	器具間隔最大限					2 . 5	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 3	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8
		横方向 (A)	縦方向 (B)	3 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 1	1 0 0	9 9	9 7	
H m	0 . 4 4 H m	0 . 4 4 H m	4 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	9 8		
			5 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	9 8		
			7 . 0	1 0 8	1 0 7	1 0 6	1 0 6	1 0 7	1 0 6	1 0 5	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 2	9 9		
			1 0 . 0	1 0 8	1 0 8	1 0 7	1 0 7	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	9 9		

